

Bid Notice Abstract

Request for Quotation (RFQ)

Reference Number

10190848

Procuring Entity

PHILIPPINE STATE COLLEGE OF AERONAUTICS

Title

Procurement of Refrigerator Vacuum Cleaner, Emergency Light, and Exhaust Fan for VAB,

FAB, and BAB Campus.

Area of Delivery

Metro Manila

Solicitation Number:	2023-09-0129	Status	Pending
Trade Agreement:	Implementing Rules and Regulations		
Procurement Mode:	Negotiated Procurement - Small Value Procurement (Sec. 53.9)	Associated Components	1
Classification:	Goods	Bid Supplements	0
Category:	Appliances		
Approved Budget for the Contract:	PHP 103,000.00	Document Request List	0
Delivery Period:	15 Day/s		
Client Agency:			
		Date Published	05/10/2023
Contact Person:	Romualdo Salud Intia		
	Canvasser Piccio Garden Villamor Airbase Pasay City Metro Manila	Last Updated / Time	04/10/2023 10:21 AM
	Philippines 1300 63-02-4255326 63-02-4255326 mhaldz123@gmail.com	Closing Date / Time	09/10/2023 09:00 AM

Description

1. 1 unit REFRIGERATOR 1.8 cu.ft Bar Fridge Single Door RB-18HS Heavy duty quality Energy efficient composser R600a refigerant Consumes only 61 watts With freezer compartment Wire Shelves Anti bacterial coating reversible door stainless door color

2. 1 unit VACUUM CLEANER 25L Stainless body 3in1 function (wet/Blow/Dry) Stainless steel tank with sponge filter waterproof switch super function power for dirty water 220v 60hz 1200w Airflow rate: 1.5m/min Sunction hose length:1.5m Noise level: 78dB Heavy duty / Japan Design

3. 33 units EMERGENCY LIGHT

Wall or ceiling mounted
Fully adjustable LED heads comply with safety codes in a compact housing
Quick connect back-plate offers ease of mounting.

120/277 voltage operation

120/277 voltage operation
Housing-Injection-molded, engineering-grade, SVA flame retardant, high-impact, thermoplastic in white.
Illumination-Long lasting, effecient ultra-bright white LED lamp heads. 1 watt (8 LEDs x 0.125 watt) per head. Highperformance chrome plated metalized refelctor and plastic lens for optional light distribution. Adjustable LED lamp
heads provide optional center-to-center spacing. high-lumen option available for increased center-to-center spacing.
Electrical-Dual 120/277 voltage. Charge rate/power "ON" LED indicator light and push to test switch for mandated
code compliance testing. Long-life maintenance-free, rechargeable NiCd battery. Internal solid-state transfer switch
automatically connects the internal battery to LED lamp heads for minimum 90-minute emergency illumination. fully
automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

4. 1 piece EXHAUST FAN 12" Plastic blade with shutters with thermal fuse protection 340mm x 340mm dimension 55W wattage Air delivery: 636 cu.ft/min Other Information
All quotations to be submitted only to the Official e-mail address of Procurement Officer Addressed to the Acting Procurement Officer email Add: phiscaprocurement@gmail.com Asso. Prof. Mary Ann A. Vista

Created by

Romualdo Salud Intia

Date Created

Acting Procurement Officer

04/10/2023